

INTEGRATED DOOR CLOSER a MANTION innovation

Access gate self closing system. Ideal for public area!





MANTION S.A.S

7, rue Gay Lussac - ZI de Trépillot 25000 Besançon - FRANCE Tel. +33 3 81 50 56 77 - Fax. +33 3 81 53 29 76 Mail: export@mantion.com


Web: www.mantion.com

temperature

Door closer for access door up to **200 kg** Integrated closing device: to avoid degradation

VARIATION IN CLOSING TIMES BETWEEN -10°C AND 35°C

25312 DT - 25312 GT: 14 sec. (77 sec. for classic version) **25322 DT - 25322 GT: 28 sec.** (232 sec. for classic version)



Item Nr.		Color	Dimensions of the door			Gate	Closing	Maximum
			Width	Height	Thickness	weight	strength	opening angle
253120	Right opening	Khaki	1000 mm (Max)	2000 mm (Max)	40 mm (Min)	85 Kg (Max)	16 Nm	180° single action
253120	T Left opening	Grey						
253220	Right opening	Khaki	1800 mm (Max)	2400 mm (Max)	50 mm (Min)	200 Kg (Max)	49 Nm	180° single action
253220	Left opening	Grey						

KITS AVAILABLE FOR USE WITH DOORS OR GATES (SCREW- OR WELD-TYPE)

DOORS KITS:

25312DT / 25312GT : 85 Kg max. 25322DT / 25322GT : 200 Kg max.

door-only upper pivot delivered with the kit



KITS FOR GATES: screwing type:

25312DT52 / 25312GT52 : 85 Kg max.

gate-only screw-type upper pivot delivered with the kit



KITS FOR GATES: welding type:

25312DT51 / 25312GT51: 85 Kg max.

gate-only weld-type upper pivot delivered with the kit



EASY SPEED ADJUSMENT

By moving the adjusting wheel in both direction. High precision and large range of adjustment.

SMOOTH CLOSING

The hydraulic mechanism of this door closer guarantees a silent and smooth closing for all kinds of gates and doors and a durability of over 500 000 opening/closing cycles.

ADJUSTABLE CLOSING STRENGHT

Through adjustment of the spring.

HIGH-CLOSING STRENGHT

Door or gate closure is ensured by a special high-performance spring

EASY MOUNTING

The small sized fixing plate enables the utilization of this pivot for all types of doors and gates.

SLIDING SEAT

Facilitates this installation on site.